

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 229 399 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
07.08.2002 Bulletin 2002/32

(51) Int Cl.7: G03G 15/02, G03G 21/00

(21) Application number: 02001141.7

(22) Date of filing: 25.01.2002

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Amemiya, Ken
Tokyo (JP)
• Iwasaki, Yukiko
Yokohama-shi, Kanagawa (JP)

(30) Priority: 25.01.2001 JP 2001017150

(74) Representative: Schwabe - Sandmair - Marx
Stuntzstrasse 16
81677 München (DE)


(71) Applicant: Ricoh Company, Ltd.
Tokyo 143-8555 (JP)

(54) Cleaning device and image forming apparatus

(57) A cleaning device (18) including a brush roller (12) that contacts the surface of a charge roller (2) for cleaning it and an image forming apparatus including the cleaning device are disclosed. The brush roller (12)

has a brush (20) contacting the charge roller (2) due to the weight of the brush roller. The brush roller (12) rotates by following the rotation of the charge roller (2). The cleaning device (18) has a simple configuration while the brush roller (12) has high durability.

Fig. 2



EP 1 229 399 A1

Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to a copier, printer, facsimile apparatus or similar image forming apparatus and more particularly to a cleaning device for an image forming apparatus.

Description of the Background Art

[0002] A cleaning device for cleaning a desired member has customarily been used in machines and apparatus in various fields. An image forming apparatus, for example, includes a cleaning device for cleaning the surface of an image carrier, a cleaning device for cleaning the surface of a charge roller that charges the image carrier, and a cleaning device for cleaning the surface of an image transfer belt.

[0003] Japanese Patent Laid-Open Publication No. 7-140763, for example, discloses a cleaning device using a brush roller that contacts the surface of a member to be cleaned. The brush roller is rotated by a drive source. A brush on the brush roller and the surface of the member to be cleaned each are moved at a particular linear velocity, so that the brush scrapes off impurities deposited on the member.

[0004] However, the conventional brush roller type of cleaning device needs the drive source for driving the brush roller. Moreover, this type of cleaning device needs means for limiting the amount of bite of the brush into the desired member in order to control the permanent deformation of the brush. This increases the cost of the cleaning device and makes the cleaning device sophisticated. It is to be noted that the amount of bite of the brush refers to the maximum amount of deformation of the brush roller to occur in the radiation direction when the brush is pressed against the surface of the desired member. It has been customary to control the yield of the brush by confining the amount of bite in an adequate range.

[0005] Technologies relating to the present invention are also disclosed in, e.g., Japanese Patent Laid-Open Publication Nos. 8-22173, 10-206696, 10-282854 and 11-219048.

SUMMARY OF THE INVENTION

[0006] It is an object of the present invention to provide a cleaning device free from the problems discussed above.

[0007] It is another object of the present invention to provide a unit including the cleaning device.

[0008] It is still another object of the present invention to provide an image forming apparatus including the cleaning device.

[0009] It is a further object of the present invention to provide a brush roller capable of reducing the yield of its brush and usable over a long period of time.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

FIG. 1 is a section showing an image forming apparatus embodying the present invention;

FIG. 2 is an enlarged view of a brush roller included in the illustrative embodiment;

FIG. 3 is a front view showing the brush roller; and FIG. 4 is a view showing a positional relation between the brush roller and a member to be cleaned thereby.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0011] Referring to FIG. 1 of the drawings, an image forming apparatus embodying the present invention is shown and includes a charge roller 2 to be cleaned. The image forming apparatus has one or more of an electronic copier function, a printer function, and a facsimile apparatus function. As shown, the image forming apparatus includes an image carrier implemented as a photocopied drum 1. On the start of an image forming cycle, the drum 1 is caused to rotate in a direction indicated by an arrow A in FIG. 1. The charge roller 2 is located to face the surface of the drum 1. A drive source, not shown, or the drum 1 in rotation causes the charge roller 2 to rotate in a direction indicated by an arrow B. The charge roller 2 is made up of a metallic core 3 and an elastic body 4 affixed to the core 3. While the charge roller 2 is in rotation, a voltage of preselected polarity is applied to the charge roller 2 to thereby charge the surface of the drum 1 to the preselected polarity.

[0012] A laser writing unit, not shown, scans the charged surface of the drum 1 with a laser beam LB in accordance with image data, thereby forming a latent image on the drum 1. A developing device 5 develops the latent image with toner to thereby produce a corresponding toner image. More specifically, in the illustrative embodiment, the developing device 5 includes a casing 6 storing a powdery developer D and a sleeve 7 for conveying the developer D deposited thereon. While the sleeve 7 is rotated in a direction indicated by an arrow C in FIG. 1, toner contained in the developer is electrostatically transferred from the sleeve 7 to the latent image, developing the latent image.

[0013] An image transfer belt (simply belt hereinafter) 8 faces the drum 1 and moves in a direction indicated by an arrow E in FIG. 1. The belt 8 conveys a sheet or recording medium P fed from a sheet feed section not shown. When the sheet P passes through an image

transfer position between the drum 1 and the belt 8, a voltage for image transfer is applied to an image transferring device 9, which faces the drum 1 with the intermediary of the belt 8. The image transferring device 9 electrostatically transfers the toner image from the drum 1 to the sheet P. If desired, the toner image may be transferred from the drum 1 to the sheet P by way of an intermediate image transfer body.

[0014] A cleaning brush 10 and a cleaning blade 11 remove the toner left on the drum 1 after the image transfer. On the other hand, a fixing device, not shown, fixes the toner image with heat and pressure.

[0015] In the illustrative embodiment, the image carrier, charge roller 2, cleaning brush 10 and a brush roller 12, which will be described later, are rotatably mounted on a unit case 13. Further, the base end of the cleaning blade 11 is affixed to the unit case 13, completing a single unit 14. The unit 14 is movable into and out of the apparatus body along guide rails 15, as needed. The cleaning brush 10, cleaning blade 11 and a cleaning case 16, which is part of the unit case 13, constitute a cleaning device 17 for cleaning the surface of the drum 1.

[0016] As shown in FIG. 1, the charge roller 2 for charging the drum 1 is held in contact with the surface of the drum 1. Alternatively, the charge roller 2 may be slightly spaced from the surface of the drum 1, if desired.

[0017] During image forming operation, toner undesirably passed the cleaning blade 11 and impurities flying about inside the apparatus body and including toner deposit on the surface of the charge roller 2. Such toner and impurities would make the charging of the drum 1 irregular or defective and would thereby lower the image quality of the resulting toner image.

[0018] The illustrative embodiment solves the above problem with a cleaning device 18 assigned to the charge roller 2 and including the brush roller 12. The brush roller 12 extends in parallel to the charge roller 2. As best shown in figs. 2 and 3, the brush roller 12 is made up of a rigid core 19 formed of metal or resin and a brush 20 having a number of filaments, which are affixed to the core 19 at base portions thereof. The brush 20 extends over the entire circumference of the core 19 over an axial range W shown in FIG. 3. The brush 20 is held in contact with the charge roller 2, which is a member to be cleaned.

[0019] The brush roller 12 is configured such that the brush 20 contacts the surface of the charge roller 2 due to the weight of the brush roller 12. The charge roller 2 in rotation causes the brush roller 12 to rotate in a direction indicated by an arrow G in FIGS. 1 and 2.

[0020] More specifically, as shown in FIGS. 1 and 2, the unit case includes a rear side wall 13A and a front side wall, not shown, to each of which a bearing member 21 is affixed. A guide slot 22 is formed in each bearing member 21. Axially opposite ends of the core 19 of the brush roller 12 are respectively rotatably received in the guide slots 22 of the two bearing members 21. In this

position, the core 19 is slidable along the guide slots 22 in a direction indicated by an arrow F in FIG. 2, i.e., toward and away from the charge roller 2. The guide slots 22 each have a width slightly greater than the diameter of the core 19, so that the opposite ends of the core 19 are stably received in the guide slots 22 without shaking.

[0021] The brush roller 12 is positioned above the charge roller 2. This, coupled with the fact that the core 19 is slidably received in the guide slots 22, allows the brush roller 12 to rest on the surface of the charge roller 2 due to the weight of the brush roller 12. Further, because the core 19 is rotatably received in the guide slots 22, the charge roller 2 rotating in the direction B causes the brush roller 12 to rotate in the direction G. That is, the brush roller 12 follows the rotation of the charge roller 2. In this condition, the brush 20 contacting the surface of the charge roller 2 removes the toner from the above surface.

[0022] As stated above, the brush roller 12 is not driven by a drive source, but is driven by the charge roller 2. This obviates the need for an exclusive drive source and thereby simplifies the configuration of the cleaning device 18 while reducing the cost. In addition, the brush 20 does not contact the surface of the charge roller 2 with an excessive force, protecting the surface from wear.

[0023] Assume a sum of the radius of the brush roller 12 and that of the charge roller 2 in a condition in which the rollers 12 and 2 do not contact each other, and a distance between the axis of the roller 12 and that of the roller 2 in a condition in which the rollers 12 and 2 contact each other. Then, the amount of bite of the brush 20 is produced by subtracting the above distance from the above sum. If the amount of bite is excessively great, then the filaments of the brush 20 deteriorate soon and permanently deform, i.e., yield. If the amount of bite is excessively small, then the brush 20 fails to efficiently clean the surface of the charge roller 20. It has been customary to adjust the relative position between the brush roller 12 and the charge roller 2 in such a manner as to maintain the distance between them constant, thereby limiting the amount of bite. This, however, needs extra limiting means that would increase the cost of the cleaning device while complicating the configuration.

[0024] By contrast, in the illustrative embodiment, the brush roller 12 contacts the surface of the charge roller 2 due to its own weight. It follows that a desired amount of bite of the brush 20 is achievable only if the weight of the brush roller 12 is adjusted, obviating the need for the conventional limiting means. The cleaning device 18 is therefore simple in configuration and low cost.

[0025] While the length of the filaments constituting the brush 20 is open to choice, it should preferably be 2 mm or less, more preferably 0.4 mm to 0.6 mm. It should be noted that the length of the filaments excludes the portions affixed to the core 19. The filaments with such a small length successfully reduce a bending moment to act on the base portions of the filaments al-

though the filaments elastically bend in contact with the charge roller 2. The brush 20 is therefore free from yield or permanent deformation over a long period of time and achieves a long life. If the length of the filaments is greater than 2 mm, then the distance between nearby filaments at the tip increases with the result that the load to act on the individual filament contacting the charge roller 2 increases, aggravating the yield of the brush 20.

[0026] It is a common practice to remove toner collected by the end of the brush 20 with a flicker. In the illustrative embodiment, as shown in FIG. 1, it is possible to remove the toner from the end of the brush 20 without resorting to a flicker because the filaments of the brush 20 are short, as stated above. Why a flicker is needless is not clearly accounted for. Presumably, when the filaments of the brush 20 as short as 2 mm or less and elastically deformed in contact with the charge roller 2 leave the charge roller in accordance with the rotation of the brush roller 12, the filaments immediately restore their original position due to elasticity. The resulting shock causes the toner deposited on the tips of the filaments to jump off the filaments.

[0027] While the diameter and density of the filaments of the brush 20 are also open to choice, the diameter should preferably be 2 denier or below or a weight/length ratio of less than 2/9 g/km while the density should preferably be 20,000 filaments/cm² or above, more preferably 30,000 filaments/cm². With this configuration, a great number of filaments contact the charge roller 2 with the result that the load to act on the individual filament decreases. This is also successful to protect the brush 20 from yield over a long period of time. Further, the great number of filaments contacting the charge roller 2 can efficiently, uniformly clean the charge roller 2 for thereby insuring high image quality.

[0028] The weight of the brush 12, which is also open to choice, should preferably be 50 g or above, but 200 g or below, in order to guarantee the adequate bite of the brush 20 and smooth rotation of the brush roller 12. A weight below than 50 g makes the amount of bite of the brush 20 short and thereby lowers the cleaning efficiency. A weight above 200 g makes the amount of bite excessive and thereby accelerates the yield of the brush.

[0029] The brush 20 may be affixed to the core 19 by any suitable method. When the base end of the brush 20 is affixed to the core 19 by electrostatic implantation, short filaments can be densely implanted in the core 19 and are free from yield over a long period of time. For example, adhesive may be coated on the core 19 over the axial range W, in which case a number of filaments will be electrostatically adhered to the adhesive to be affixed to the core 19 via the adhesive.

[0030] The filaments of the brush 20 may be formed of any suitable material. Experiments showed that nylon 66, PET (polyethylene terephthalate) or similar resin effectively reduced the yield of the brush 20 and insured the adequate amount of bite. If desired, the filaments

may be formed of a material capable of electrostatically collecting toner from the charge roller 2 so as to further promote efficient cleaning.

[0031] Assume that the member to be cleaned is a cylindrical rotary body like the charge roller 2, FIG. 1. Then, as shown in FIG. 1, only if the brush roller 12 contacts a cylindrical body 2A anywhere in a range S above a horizontal plane H containing the axis O of the body 2A, the brush 20 can desirably contact the body 2A due to its own weight.

[0032] While the illustrative embodiment has concentrated on the charge roller 2, the cleaning device shown and described is similarly applicable to any one of the other members including the image carrier 1, belt 8, and intermediate image transfer body.

[0033] At least the cleaning device 18 and charge roller 2 or similar member to be cleaned may be constructed into the unit 14, as shown in FIG. 1. In this case, the brush 12 with filaments as short as 2 mm or less can be reduced in diameter and can therefore reduce the size of the unit 14. This is also true with an image forming apparatus including a cleaning device and a member to be cleaned.

[0034] In summary, it will be seen that the present invention provides a cleaning device including a long-life brush roller, a unit including the cleaning device, and an image forming apparatus including the cleaning device.

[0035] Various modifications will become possible for those skilled in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

[0036] Preferably, the cleaning device is constituted such that the brush (surface means) is able to rotate by following a movement of the surface. Preferably, that following of a movement is performed due to a local contact, in particular a frictional contact between the brush and the surface of a member to be cleaned. Due to the (frictional) contact between the surface of the member to be cleaned and the brush (deformable surface means), a rotational force is transferred from the surface of the member to be cleaned to the brush roller (rotatable member). Preferably, this rotational force has a component which is tangential to the circumference or rotational movement of the brush (surface means) or brush roller (rotatable member). Preferably, the brush or brush roller follows the movement of the surface of the member to be cleaned due to the local transfer of the rotational force to the brush at the location of contact. Preferably, the brush (surface means) contacts only a portion of the surface of the member to be cleaned during the movement of the surface of the member to be cleaned.

[0037] Instead of a brush roller any other rotatable member of arbitrary shape may be used which is able to perform a rotation. The rotation is preferably performed around an axis. The rotatable member may for instance have a polygonal shape. Preferably, the member has a cylindrical shape. Preferably, the surface is

deformable, in particular elastically deformable. In other words, the rotatable member comprises preferably a (elastically) deformable surface means. Preferably, this elastical deformable surface means is a brush. Instead of a brush or in combination therewith any other elastical deformable surface means like a sponge or elastically deformable layer like a rubber layer may be used. Preferably, the deformable surface means comprises a plurality of independently elastical deformable members like the filaments of brush. Preferably, the elastically deformable surface means is locally elastically deformable at the location, where a contact pressure is applied to the rotatable member. Preferably, the elastically deformable surface means is constituted such that the shape of the remaining surface to which no pressure is applied, remains unchanged.

[0038] Preferably, the cleaning device comprises a guiding means, e.g. a guiding slot. The guiding means sets or defines a path along which the rotatable member may be moved. Preferably, the guiding means is constituted such that the rotatable member may be rotated in the path, in particular while being moved. Preferably, the guiding means defines at least at portions thereof a path of predefined inclinations and/or curving. Preferably, the rotatable member comprises an axis which rotates within path defined by the guiding means. Preferably, the axis has a predetermined fit and/or distance to the boundary of the path such that a rotation is allowed if a predefined rotational force is applied to the rotatable member. Preferably, in case of contact between the axis and the boundary of the path, the boundary of the path has a predefined constitutions such that a predefined frictional force occurs between the axis and the boundary or limit of the path in case of rotation of the rotatable member.

[0039] Preferably, the axis has a predefined surface condition such that the afore-mentioned predefined frictional force occurs in case of contact between the axis and the boundary of the path. Preferably, the rotatable member has a predefined weight. Preferably, the inclination and/or the friction between the axis and the boundary of the path and/or the weight of the rotatable member results in a predetermined downward force of the rotatable member. If the surface of the rotatable member contacts a surface to be cleaned, preferably, the downward force corresponds to a contact force between the surface to be cleaned and the surface means of the rotatable member. Preferably, the surface to be cleaned and the surface of the rotatable member are constituted such that a predefined frictional force occurs in case of contact between the rotatable member and the member to be cleaned. Preferably, the contact force is such that a predetermined frictional force is caused which is sufficient to apply a rotational force from the member to be cleaned to the rotatable member in order to cause rotation of the rotatable member. Preferably, the rotational force has a component which is inclined or perpendicular to the contact force.

[0040] Preferably, the arrangement of the path and the shape of the rotatable member is such that the surface means extends beyond the end of the path before the rotatable member leaves the path. In other words, in a position, where the rotatable member is about to leave the path, the surface means projects a predetermined portion beyond the end of the path. Preferably, the predetermined portion has a length which correspond at least to a length which corresponds to the maximum elastical deformation of the surface means. Preferably, the predetermined portion is an arrange of one times to ten times of this length. Preferably, more than three times of this length.

Claims

1. A cleaning device comprising a brush roller having a brush constituted to be able to contact a surface of a member to be cleaned, said cleaning device being constituted such that said brush is able to contact said surface due to the weight of said brush roller and is able to rotate by following a movement of said surface.
2. A cleaning device comprising a rotatable member (12) having an elastically deformable surface means (20) and a guiding means (22) defining a path of movement for said rotatable member and allowing rotation of said rotatable member, **characterized in that** the guiding means and the rotatable member are constituted such that a predetermined downward force urges the rotatable member downwards along said path due to the rotatable member's own weight, said downward force corresponding to a contact force which, when applied to the surface means, results in an elastical deformation of the surface means and allows for a transfer of a rotational force to the rotatable member for causing rotation of the rotatable member.
3. The cleaning device as claimed in claim 2, wherein the rotatable member is a brush roller and the elastically deformable surface means is a brush.
4. A brush roller comprising filaments, wherein the filaments have a length of 2 mm or below, a diameter of 2 denier or below, a weight/length ratio of less than 2/9 g/km, a density of 20.000 filaments/cm² or above, and/or base portions which are affixed to a core of said brush roller by electrostatic implantation.
5. The brush roller as claimed in claim 4, wherein the brush roller has a weight of 50 g or above, but 200 g or below.
6. The cleaning device as claimed in claim 1 or 3,

wherein the brush roller is constituted as claimed in claim 4 or 5.

7. A unit comprising a member to be cleaned and the cleaning device as claimed in any of claims 1 to 3 or 6, wherein the member to be cleaned is in contact with said cleaning device. 5
8. The unit as claimed in claim 7, wherein the member to be cleaned comprises a cylindrical rotary body, and said brush contacts the surface of said rotary body at a position above a horizontal plane containing an axis of said rotary body. 10
9. The cleaning device as claimed in claim 7 or 8, wherein the member to be cleaned comprises a charge roller that faces an image carrier for charging said image carrier. 15
10. An image forming apparatus including the cleaning device of any of claims 1 to 3 or 6, the brush of claims 4 or 5, or the unit of any of claims 7 to 9. 20

25

30

35

40

45

50

55

Fig. 3





Fig. 4





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 00 1141

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 08, 30 August 1996 (1996-08-30) & JP 08 095350 A (RICOH CO LTD), 12 April 1996 (1996-04-12) * abstract; figure *	2,7-10	G03G15/02 G03G21/00
Y	---	1,3,5,6	
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 07, 31 July 1996 (1996-07-31) & JP 08 062949 A (RICOH CO LTD), 8 March 1996 (1996-03-08) * abstract; figure *	2,7-10	
Y	---	1,3,5,6	
X	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 09, 30 September 1997 (1997-09-30) & JP 09 114201 A (FUJI XEROX CO LTD), 2 May 1997 (1997-05-02) * abstract; figure *	4	
Y	---	5	
D, Y	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 09, 31 October 1995 (1995-10-31) & JP 07 140763 A (CANON INC), 2 June 1995 (1995-06-02) * abstract; figure *	1,3,5,6	
Y	PATENT ABSTRACTS OF JAPAN vol. 016, no. 252 (P-1367), 9 June 1992 (1992-06-09) & JP 04 060660 A (CANON INC), 26 February 1992 (1992-02-26) * abstract; figure *	1,3,5,6	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 8 April 2002	Examiner Götsch, S
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

FFO FORM 1503 (03.92) (P/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 1141

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-04-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 08095350	A	12-04-1996	NONE	
JP 08062949	A	08-03-1996	NONE	
JP 09114201	A	02-05-1997	US 5842081 A	24-11-1998
JP 07140763	A	02-06-1995	NONE	
JP 04060660	A	26-02-1992	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82